

Features

- 2.0L / .53G stainless steel hot tank
- 3.78L / 1G stainless steel cold tank
- High quality, high output refrigeration and heating system
- Water is dispensed through industry standard Tomlinson style faucets that allow for Hot and Cold or Cook and Cold options
- Rugged HDPE cabinet is extremely durable and easy to clean
- Removable, two-piece drip tray for easy cleaning
- · Dual mechanical float for enhanced reliability
- Filter can be easily mounted on back with bracket

- Available in black and white
- Cup dispenser (option)
- Energy Star rated
- UL listed



Inspirations®

Filtration Cooler

Power

Voltage 115, 220, 100

Frequency (Hz) 50/60

Power Consumption 4.89A / 554W / 115V Cold Power Consumption 1.44A / 118W / 115V

Hot Power Consumption 3.87A / 449W / 115V

ES (kWh/24 hrs.) 0.81 % lower than ES Standard 7%

Hot Water System

Avg. Hot Water Temp at Nozzle @77°F Ambient (Cut-in / Cut-out Temp) 166.57°F / 191.43°F

Hot Water ARI Rating 45, 6 oz > 165°F +/- 10%

Hot Thermometer / Heat Limiter 203°F +/- 5.5°F

Hot Thermostat / Thermistor Cycle 167°F +/- 11°F / 187°F +/- 4°F

Hot Water Flow Rate 0.78-0.87 oz/sec

Hot Tank Size (Liter: Gallon) 2.0L: .53G Heat Band Wattage 450W

Cold Water System

Avg. Cold Water Temp at Nozzle @ 75°F ambient (Cut-in / Cut-out Temp) 45.87°F / 42.2°F

Cold Water ARI Rating 27, 5 oz < 50°F +/- 10%

Cold Thermostat Set Point 45°F + 3°/-8°F

Cold Water Flow Rate 1.4 oz/sec

Cold Tank Size / Usable Volume / Below Baffle Cold Water (Liter: Gallon) 3.78 / 2.08 / 1.51: 1 / 0.55 / 0.4

Weights and Measurements

Net Weight: Gross Weight (H&C / C&C Lbs) Net 34.6 / 31.68: Gross 37.9 / 34.98

Max Distance from Drip Tray to Faucet (Inch: mm) 7.8:199

Faucet / Dispense Height (Inch: mm) 28.75: 730.2

Cooler Dimensions / Boxed Dimensions WxDxH (inch) 12.4x13.5x39 / 13x13.9x40

Container Load (20') 224
Container Load (40') 462

Container Load (40' HC) 462 Container Load (45" HC) 518

Certifications UL Listed

Warranty:

3 years: Sealed refigeration system

2 years: Parts (electrical to include cold controls, relay

overloads, pumps and PCB's)

(647) 381-8990 or send us an email to: demmons@applitechcanada.com

Call us at

