



GNB 215i-SIP



## Features

- 1.2L / .32G stainless steel hot tank
- 3.78L / 1G stainless steel cold tank
- Elevated dispensing height and larger dispensing area
- Hot and cold temperature indicator
- Safety lock feature for hot and cold water
- Fast flow electronic dispensing
- Chrome push buttons and accents
- Lighted spout and dispensing area
- Integrated cup dispenser (option)
- Dual mechanical float for enhanced reliability
- Optional base plate for added stability
- Available in black
- UL listed
- **Accu-Temp®** — Serves water at the proper temperature every time
- **iBoil** — Increases the hot water temperature to just under boiling—perfect for barista quality coffee, teas, and cooking noodles and soups
- **SIP®** — Enhanced sanitization sanitizes cold reservoir, waterways and spout
- **Stay-Cool®** — Keeps residual water in the cold waterway chilled and ready to serve



Reliably Serving A Thirsty World



## Power

Voltage	115, 220, 100
Frequency (Hz)	50/60
Power Consumption	5.42A / 602W / 110V
Cold Power Consumption	1.44A / 118W / 110V
Hot Power Consumption	4.33A / 500W / 110V
ES (kWh/24 hrs.)	0.699
% lower than ES Standard	19.6%

## Hot Water System

Avg. Hot Water Temp at Nozzle @77°F Ambient (Cut-in / Cut-out Temp)	175.3°F / 184.93°F
Hot Water ARI Rating	45, 6 oz > 165.2°F +/- 10%
Hot Thermometer / Heat Limiter	203°F +/- 37.4°F
Hot Thermostat / Thermistor Cycle	172.4°F – 190.4°F
i-Boil Set Point	192.2°F
Avg. Temp of iBoil at Nozzle @ 75°F Ambient (Cut-out Temp)	202.8°F
Hot Water Flow Rate	1.42 oz/sec
Hot Water Flow Rate (oz per sec) w/Accu-Temp Delay	1.27 oz/sec
Hot Tank Size (Liter : Gallon)	1.2L : .32G
Heat Band Wattage	520W

## Cold Water System

Avg. Cold Water Temp at Nozzle @ 75°F ambient (Cut-in / Cut-out Temp)	43.93°F / 41.32°F
Cold Water ARI Rating	27, 5 oz < 50°F +/- 10%
Cold Thermostat Set Point	45°F + 35.6°/-39.2°F
Cold Water Flow Rate	1.52 oz/sec
Cold Water Flow Rate (oz per sec) w/ Accu-Temp Delay	1.37 oz/sec
Cold Tank Size / Usable Volume / Below Baffle Cold Water (Liter : Gallon)	3.78 / 2.84 / 1.5 : 1 / .75 / .39

## SIP® Sanitization

Sanitization Duration	40 Minutes
Frequency	Once a day, and programmable
Auto Sanitization Mode	Sanitizes cold tank, hot tank and waterways
Manual Sanitization Mode	Sanitizes cold tank, hot tank, waterways and nozzle

## Weights and Measurements

Net Weight : Gross Weight (Lbs)	36.6 : 38.8
Max Distance from Drip Tray to Faucet (Inch : mm)	10 : 254
Faucet / Dispense Height (Inch : mm)	37.5 : 952.5
Cooler Dimensions / Boxed Dimensions WxDxH (inch)	11.65x15x43.5 / 12.6x14x44.5
Container Load (20') : (40')	224 : 456
Container Load (40' HC) : (45' HC)	456 : 532
Certifications	UL Listed

### Warranty:

3 years: Sealed refrigeration system  
2 years: Parts (electrical to include cold controls, relay overloads, pumps and PCB's)

10/2016

Nexus trademark owned by MTN Products. ©2016 MTN Products. All rights reserved.

phone: 909-629-7301  
Canada: 905-302-7896  
email: sales@mtnproducts.com  
web: mtnproducts.com



Reliably Serving A Thirsty World