

Features

- 2L / .53G stainless steel hot tank
- 11.4L / 3G stainless steel cold tank
- Larger dispensing area for sport bottles & carafes
- Gravity dispensing
- Dual mechanical float
- Hot water child safety lock
- Room for internal mounting of an icon eco3 filter (single or dual) or RO system (75 GPD) (Sold Separately)

- Injection molded ABS
- Removable, dishwasher safe drip tray
- Stylish design fits in any office environment
- Custom colors and logos can be made available
- UL listed





Power

Voltage 115, 220, 100

Frequency (Hz) 50/60

Power Consumption Tatung compressor 4.89A / 563W / 115V

Huayi compressor 4.05A / 520W / 115V

Cold Power Consumption Tatung compressor 1.44A / 118W / 115V

Huayi compressor 0.8A/ 70W/115V

Hot Power Consumption 3.87A / 449W / 115V

ES (kWh/24 hrs.) 0.85kwh / 24h

% lower than ES Standard 2.3%

Hot Water System

Avg. Hot Water Temp at Nozzle @77°F Ambient (Cut-in /Cut-out Temp) 175.28°F / 188.17°F

Hot Water ARI Rating 46, 6oz > 165°F +/- 10%

Hot Thermometer / Heat Limiter 203°F +/- 5.5°F Hot Thermostat / Thermister Cycle 168.8°F – 186.8°F

Hot Water Flow Rate 0.73 oz/sec
Hot Tank Size (Liter: Gallon) 2L:.53G

Heat Band Wattage 450W

Cold Water System

Avg. Cold Water Temp at Nozzle @ 75°F ambient (Cut-in /Cut-out Temp) 41.57°F / 41.37°F

Cold Water ARI Rating 29, 5oz < 50°F +/- 10%

Cold Thermostat Set Point 45°F + 3°/-8°F

Cold Water Flow Rate 0.95 oz/sec

Cold Tank Size / Usable Volume / Below Baffle Cold Water (Liter: Gallon) 11.35 / 9/46 / 3.36L: 3 / 2.5 / 0.89G

Weights and Measurements

Net Weight / Gross Weight (Lbs) 54.67 / 58.67

Max Distance from Drip Tray to Faucet (Inch: mm) 10:254

Faucet / Dispense Height (Inch: mm) 35.5:901.7

Cooler Dimensions / Boxed Dimensions WxDxH (inch) 12.5x15.3x44.6 / 13.2x16.2x45.7

Container Load (20') / (40') 186 / 383 Container Load (40' HC) / 45' HC) 383 / 432

Certifications UL Listed

Filter Compartment Dimensions

Width (Inch: mm) 10.75: 273

Inside Top to Bottom (Inch: mm) 17.5:444

Center Bracket to Bottom (Inch: mm) 15:381

Depth without Bracket (Inch: mm) 43:1092

Depth with Bracket (Inch: mm) 43:1092

Warranty:

3 years: Sealed refigeration system

2 years: Parts (electrical to include cold controls, relay

overloads, pumps and PCB's)

phone: 909-629-7301 Canada: 905-302-7896

email: sales@mtnproducts.com

web: mtnproducts.com



10/2016