

Features

- 1.2L / .32G stainless steel hot tank
- 3.78L / 1G stainless steel cold tank
- Elevated dispensing height and larger dispensing area
- Hot and cold temperature indicator
- Safety lock feature for hot and cold water
- Fast flow electronic dispensing
- Chrome push buttons and accents
- · Lighted spout and dispensing area
- Integrated cup dispenser (option)
- Optional base plate for added stability

- Available in black
- UL listed
- Accu-Temp® Serves water at the proper temperature every time
- NoLeak® EZ-Fill® Patented no-spill adapter for use with no-spill bottle caps
- Stay-Cool® Keeps residual water in the cold waterway chilled and ready to serve











Power

Voltage 115, 220, 100

Frequency (Hz) 50/60

Power Consumption 5.42A / 602W / 110V
Cold Power Consumption 1.44A / 118W / 110V
Hot Power Consumption 4.33A / 500W / 110V

ES (kWh/24 hrs.) 0.691 % lower than ES Standard 20%

Hot Water System

Avg. Hot Water Temp at Nozzle @77°F Ambient (Cut-in / Cut-out Temp) 175.3°F / 184.93°F

Hot Water ARI Rating 45, 6 oz > 165.2°F +/- 10%

Hot Thermometer / Heat Limiter 203°F +/- 37.4°F Hot Thermostat / Thermistor Cycle 172.4°F - 190.4°F

Hot Water Flow Rate 1.42 oz/sec

Hot Water Flow Rate (oz per sec) w/Accu-Temp Delay 1.27 oz/sec

Hot Tank Size (Liter: Gallon) 1.2L: .32G
Heat Band Wattage 520W

Cold Water System

Avg. Cold Water Temp at Nozzle @ 75°F ambient (Cut-in / Cut-out Temp) 43.93°F / 41.32°F

Cold Water ARI Rating 27, 5 oz $< 50^{\circ}F +/- 10\%$ Cold Thermostat Set Point 45°F + 35.6°/-39.2°F

Cold Water Flow Rate (oz per sec) w/ Accu-Temp Delay 1.37 oz/sec

Cold Tank Size / Usable Volume / Below Baffle Cold Water (Liter: Gallon) 3.78 / 2.84 / 1.5: 1 / .75 / .39

Weights and Measurements

Net Weight: Gross Weight (Lbs) 36.6: 38.8

Max Distance from Drip Tray to Faucet (Inch: mm) 10:254

Faucet / Dispense Height (Inch: mm) 37.5: 952.5

Cooler Dimensions / Boxed Dimensions WxDxH (inch) 11.65x15x43.5 / 12.6x14x44.5

Container Load (20') 224
Container Load (40') 456
Container Load (40' HC) 456
Container Load (45" HC) 532

Certifications UL Listed

Warranty:

3 years: Sealed refigeration system

2 years: Parts (electrical to include cold controls, relay

overloads, pumps and PCB's)

phone: 909-629-7301 Canada: 905-302-7896 email: sales@mtnproducts.com

email: sales@mtnproducts.com web: mtnproducts.com

